

Kodak

Versamark DS5340 and DS5222 Printing Systems

The **Kodak Versamark DS5340 and DS5222 Printing Systems**, each of which is comprised of a reliable printhead driven by the **Kodak Versamark CS150 System Controller**, give you powerful solutions that help your company profit from a competitive edge in the Addressing market.

Fast and flexible in-house addressing

With excellent reliability in high-data-rate environments and seamless workflow connections to third-party controllers, the **Kodak Versamark DS5340 and DS5222 Printing Systems** offer the ultimate in adaptable addressing and promise quick turnaround time for customers.

Streamlined integration with current equipment configurations allows you to leverage your existing investments while adding new capabilities.

UTS versions are available in a pay-by-usage model, which is comparable to thermal inkjet equipment and allow for lower acquisition costs.

Additionally, options for spot color enable production of higher-impact communications.

Broaden your addressing capabilities

The DS5340 and DS5222 Printing Systems deliver production-proven features that help you meet high-volume requirements:

- ▶ **More applications, more potential for profit:** Ideal for higher-value applications requiring barcoding, numbering, addressing, personalization, or spot color, such as direct mail solicitation, tags and labels, forms, and booklets
- ▶ **Add to your bottom line:** Low acquisition and operating costs
- ▶ **Meet precise customer needs:** Features a wide variety of inks, including custom colors
- ▶ **Easily integrate into your existing workflow:** Robust and reliable controller options let you meet your specific application requirements
- ▶ **No-fuss setup:** Mounting flexibility facilitates printing at any angle

A legacy of success

The DS5340 and DS5222 Printing Systems are part of a comprehensive family of highly reliable and innovative inkjet printing solutions. By leveraging the rich heritage of Kodak, the powerful **Kodak Versamark D-Series Printing Systems** help you build a more productive and profitable business and establish a new advantage.



Kodak Versamark DS5340 and DS5222 Printing Systems

- ▶ 1.07" (2.7 cm) (DS5340) or 2.13" (5.4 cm) (DS5222) imprint widths
- ▶ Up to 1,000 fpm (305 mpm)
- ▶ 120 x 120 or 120 x 240 dpi

Kodak Versamark DS5340 and DS5222 Printing Systems

Technical Data

Printheads

Printheads are replaceable components that connect to the print station through an umbilical.

DS5340: Resolutions are either 240 x 240 or 240 x 480 dpi, user selectable

DS5222: Resolutions are either 120 x 120 or 120 x 240 dpi, user selectable

Printhead physical specification

Height:	11.94" (30.32 cm)
Width:	DS5340: 2.40" (6.11 cm) DS5222: 3.94" (7.47 cm)
Depth:	5.70" (14.49 cm) (Prints at any angle)
Print width:	DS5340: 1.06" (2.71 cm) DS5222: 2.13" (5.41 cm)
Resolution:	120 x 120 or 120 x 240 dpi
Image speed:	Up to 1,000 fpm (305 mpm), based on application

Umbilical

Standard umbilical:

- Length: 12' (3.6 m)
- Outside diameter: 1.312" (3.33 cm)
- Weight: 17 lbs. (7.373 kg) with printhead attached

Optional umbilical:

- Length: 24' (7.3 m)
- Outside diameter: 1.312" (3.33 cm)
- Weight: 24 lbs. (10.91 kg) with printhead attached

Options

UTS pay by usage feature

Adjustable arm, roll-around printhead stand

Label base printhead mount

Data interface: Ethernet

DS5340: Flash card for custom font downloads

DS5340: Hand-held remote for enhanced operator convenience

Printing system physical/electrical

Cabinet:

- Height: 36" (91.44 cm)
- Width: 22" (55.88 cm)
- Depth: 32.37" (82.23 cm)
- Weight: 105 lbs. (48 kg)

Power:

- 100/120/200/220/230/240 VAC
- 10 amp
- 50/60 Hz
- 3-wire, single-phase (U.S.)

Printer physical/electrical

Cabinet:

- Height: 18.50" (46.99 cm)
- Width: 17.75" (45.08 cm)
- Depth: 23.62" (60 cm)
- Weight: 100 lbs. (45 kg)

DS5222 optional base cabinet:

- Height: 17" (43.18 cm)
- Width: 17.75" (45.08 cm)
- Depth: 23.37" (59.37 cm)
- Weight: 100 lbs. (45 kg)

Power:

- 100/120/200/220/230/240 VAC
- 6 amp
- 50/60 Hz
- 3-wire, single-phase (U.S.)

Environmental operating ranges

For Environments with Relative humidity: 10%-90% non-condensing, the temperature range is: 60°F-85°F (15.6°C-29.4°C)

For Environments with Relative humidity: 10%-60% non-condensing, the temperature range is: 86°F-104°F (30°C-40°C)

To learn more about solutions from Kodak:

Visit: graphics.kodak.com

In North America, call +1-866-563-2533

Printed using **Kodak** Technology.

Eastman Kodak Company
343 State Street
Rochester, NY 14650 USA

©Kodak, 2008. Kodak and Versamark are trademarks of Kodak.

Subject to technical change without notice.

U.CIJ.022.0808.en.04

