

Kodak

Versamark DS5240 Printing System

The **Kodak Versamark DS5240 Printing System**, comprised of a reliable printhead and the **Kodak Versamark CS150 System Controller**, gives you a powerful solution that helps your company profit from a competitive edge in the Addressing market.

High-resolution addressing for exacting customer needs

The **Kodak Versamark DS5240** printhead allows you to establish a new advantage with its high-resolution, rapid-speed, letter-quality addressing capabilities. Additionally, the DS5240 gives you the option of adding spot color for higher-impact communications.

The DS5240 allows you to meet addressing needs in-house quickly and efficiently. With low operating costs and mounting flexibility that facilitates easy integration with current equipment configurations, you can leverage existing investments and boost your bottom line.

Capitalize on new opportunities

The DS5240 Printing System delivers production-proven features that help you meet high-volume requirements:

- ▶ **Extended application range can increase value:** Ideal for higher-value applications requiring barcoding, numbering, addressing, personalization, or spot color
- ▶ **Meet precise customer needs:** Flexibility in both font selection and positioning and a broad selection of available inks, including custom colors, lets you cater to exacting customer requests
- ▶ **Easily integrate into your existing workflow:** Robust and reliable controller options let you meet your specific application requirements
- ▶ **Help increase profits:** Low acquisition and operating costs
- ▶ **No-fuss setup:** Mounting flexibility facilitates printing at any angle

A legacy of success

The DS5240 Printing System is part of a comprehensive family of highly reliable and innovative inkjet printing solutions. By leveraging the rich heritage of Kodak, the powerful **Kodak Versamark D-Series Printing Systems** helps you build a more productive and profitable business and establish a new advantage.



Kodak Versamark DS5240 Printing System

- ▶ 1.07" (2.7 cm) imprint width
- ▶ Up to 1,000 fpm (305 mpm)
- ▶ 240 x 240 or 240 x 480 dpi

Kodak Versamark DS5240 Printing System

Technical Data

Printheads

Printheads are replaceable components that connect to the print station through an umbilical. Resolutions are either 240 x 240 or 240 x 480 dpi, user selectable.

Printhead physical specification

Height:	11.94" (30.32 cm)
Width:	1.98" (5.03 cm)
Depth:	5.13" (13.03 cm) (prints at any angle)
Print width:	1.07" (2.71 cm)
Resolution:	240 x 240 or 240 x 480 dpi
Image speed:	Up to 1,000 fpm (305 mpm), based on application

Umbilical

Standard umbilical:

- Length: 12' (3.6 m)
- Outside diameter: 1.312" (3.33 cm)
- Weight: 17 lbs. (7.373 kg) with printhead attached

Optional umbilical:

- Length: 24' (7.3 m)
- Outside diameter: 1.312" (3.33 cm)
- Weight: 24 lbs. (10.91 kg) with printhead attached

Options

- Ethernet interface for connection to a variety of controllers
- Flash card for custom font downloads
- Hand-held remote for enhanced operator convenience
- Adjustable arm, roll-around printhead stand
- Label base printhead mount

Printing system physical/electrical

Cabinet:

- Height: 36" (91.44 cm)
- Width: 22" (55.88 cm)
- Depth: 32.37" (82.23 cm)
- Weight: 105 lbs. (48 kg)

Power:

- 100/120/200/220/230/240 VAC
- 10 amp
- 50/60 Hz
- 3-wire, single-phase (U.S.)

Printer physical/electrical

Cabinet:

- Height: 18.50" (46.99 cm)
- Width: 17.75" (45.08 cm)
- Depth: 23.62" (60 cm)
- Weight: 100 lbs. (45 kg)

Power:

- 100/120/200/220/230/240 VAC
- 6 amp
- 50/60 Hz
- 3-wire, single-phase (U.S.)

Environmental operating ranges

For environments with relative humidity: 10%-90% non-condensing, the temperature range is: 60°F-85°F (15.6°C-29.4°C)

For environments with relative humidity: 10%-60% non-condensing, the temperature range is: 86°F-104°F (30°C-40°C)

To learn more about solutions from Kodak:

Visit: graphics.kodak.com
Or in North America, call +1-866-563-2533

Printed using **Kodak** Technology.

Eastman Kodak Company
343 State Street
Rochester, NY 14650 USA

©Kodak, 2008. Kodak and Versamark are trademarks of Kodak.

Subject to technical change without notice.

U.CIJ.006.xxxx.xx.03

